

STATOP 500 Series PID CONTROLLERS



- Simple, intuitive configuration
- Customizable messages
- Multiple configurable logic functions
- Advanced setpoint programmer



Measure up



STATOP 500 Series

Advantages & specific features

New generation of
process controllers
technological adva

High-level series

The STATOP 500 Series PID controllers form a family of products designed to control the temperature and other physical quantities (pressures, flow-rates, etc.) in industrial processes and manage the positioning of power-operated valves.

The 500 Series is a complete range of 3 high-performance models: STATOP 548 - 589 - 596. They are distinguished by their dimensions (1/16, 1/8 and 1/4 DIN), the amount of information displayed and the number of logic inputs offered.

Simple configuration

Configurable without the user's manual in just 7 steps and only a few minutes, directly using the controller keypad or with the PYROtools configuration software on a PC.

Advanced, customizable functions

The 500 Series offers a large number of functions such as the setpoint programmer, logical blocks, the timer, the energy monitor and alerts for preventive maintenance. Because they are configurable, these can be saved and reused for future applications.

Universal solution

With their universal input and Modbus RTU communication, the 500 Series is easy to integrate into all command systems or programmable logic controllers (PLCs).

Intuitive use

Equipped with a backlit LED display indicating all the process information, the 500 Series is simple and intuitive to use for any operator.

Smart display

More than 300 preconfigured and customizable alphanumeric messages provide clear, precise information on the process such as: diagnostics, alarms, process status.

Examples of display texts: **ALARM**, **HEAT**, **4-20 MA**,



Clear,
simple
operator
interface

industrial temperature and equipped with the latest nces

More than just a simple controller...

With their logical blocks and their monitoring functions, the STATOP 500 Series can replace a small PLC or an energy monitor.

Control of energy costs

Equipped with an internal energy monitor, the STATOP 500 Series models calculate and indicate your energy consumption on the process tested, in kW and/or €.

Integrated maintenance system


Particularly useful for programming preventive maintenance operations, the STATOPs handle counting of the commands and programming of the alarm thresholds. The operator is informed of the maintenance to be performed on the actuators by a message on the display.

PYROtools assistant

The PYROtools software can be used to set up an extended configuration, create working recipes and update the controller's firmware via a PC without having to power the controller.



All the information at a glance!



APPLICATIONS

Temperature & processes

The 500 Series is a number of function work in the field

Choice of control type

The STATOP 500 models offer a choice between simple on-off control and PID control with the possibility of step-by-step valve control.

Quick, precise control



Thanks to extremely fast processing of the measurement in 120 or 60 ms, the sampling interval of the 500 Series enables a quick reaction to any change in your process.

Optimization of the settings

Advanced **tuning algorithms** guarantee optimum, stable settings, including with critical or extra-fast thermal systems. Depending on your control needs, these settings can be activated manually or automatically.

Fault detection

Complete diagnostics are performed if:

- ✓ the probe breaks or is connected incorrectly,
- ✓ the load is totally or partially cut off,
- ✓ there are variables outside the range and anomalies in the control loop.




If a fault is reported quickly, it helps to limit production losses and achieve energy savings.

Functional application blocks

Sixteen AND, OR or Timer functional blocks can be used to create customizable logical sequences in order to ensure comprehensive, flexible control of the machine.

The controller's hardware resources are fully exploited, without requiring additional external equipment (e.g. timers and small PLCs).



Timer




Three types of timer can be used to define:

- ✓ wait times before activation of the setting,
- ✓ setpoint hold times,
- ✓ scheduled setpoint changes.

Control of power-operated valves

The 500 Series is equipped with algorithms for controlling power-operated valves. This function can be used to manage **adjustment of the valves without feedback**. This practical function means that the valve's position is calculated and displayed on screen.




quipped with a large s for more effective

Setpoint programmer



The temperature profiles can be programmed with up to 12 steps and can be grouped and stored in 4 programs, with programmable ramps, holds and event inputs and outputs.

The programmer function helps to avoid temperature overruns and ensure a smooth transition when passing from one setpoint to another.



Remote configuration & control with PYROtools

The PYROtools software allows you to:

- ✓ read and write the configuration of the controller,
- ✓ store the recipes on a PC,
- ✓ display in graphic form all the parameters used by the Programmer function,
- ✓ display/configure logical operations,
- ✓ configure the parameters of the user configuration menu,
- ✓ configure alphanumeric messages,
- ✓ download Firmware upgrades



Energy monitor



The **Energy Monitor function** can be used to calculate and monitor energy consumption, estimate energy costs and report any anomalies. Values indicated: in kW and/or in €.

Preventive maintenance



This controller function allows you to monitor the life cycle of the actuators. It calculates the number of operations executed by the actuator or the duration of component operation. When compared with the average life cycle of the actuator, these data enable you to program its replacement preventively.

Large number of alarm and threshold functions



The alarms monitor the measurements and/or the difference between the setpoint and the measurement, with the possibility of linking up to **4 programmable alarms** to an output. They ensure:

- ✓ protection of the production goods and the installation,
- ✓ quality monitoring by early detection of deviations from the optimum values and triggering of an alarm in the event of threshold overruns.

PID CONTROLLERS - 500 SERIES


TECHNICAL SPECIFICATIONS

		STATOP 548		STATOP 589		STATOP 596		
OPERATOR INTERFACE								
DISPLAY	Type	LCD with black background						
	Screen area (L x H)	35 x 30 mm			37x 68 mm		83x68 mm	
	Lighting	Backlit with LEDs, life > 40,000 hours @ 25 °C						
	PV display	Number of digits: 4 to 7 segments, with decimal point Digit height: 17 mm; Color: white or “custom”				Number of digits: 4 to 7 segments, with decimal point. Digit height: 23 mm; Color: white or “custom”		
	SV display	Number of digits: 5 to 14 segments, with decimal point. Digit height: 7.5 mm; Color: green or “custom”			Number of digits: 4 to 7 segments, with decimal point. Digit height: 14 mm; Color: green or “custom”		Number of digits: 4 to 7 segments, with decimal point. Digit height: 11 mm; Color: green or “custom”	
	F display				Number of digits: 5 to 14 segments, with decimal point. Digit height: 9 mm; Color: amber or “custom”		Number of digits: 7 to 14 segments, with decimal point. Digit height: 9 mm; Color: amber or “custom”	
	Unit of measurement	Selectable, °C, °F or custom 1; Color: same as PV display						
	Controller state signals	Number: 6 (RUN, MAN, _/_, REM, SP1/2), Color: amber						
	Output state signals	Number: 4 (1, 2, 3, 4) Color: red						
	Bargraph indicator, configurable				Type: graphic bargraph,11 segments Power indication: 0...100% or -100...100% Current indication: 0...100% f.s. Valve position indication: 0...100%			
KEYPAD		Number of keys: 4 silicon (Man/Auto, INC, DEC, F), Type: mechanical				Number of keys: 6 silicon (Man/Auto, L/R,*, INC, DEC, F)		
INPUTS								
MAIN INPUT	Sensor type	TC, RTD (PT100, JPT100), IR ES1B, DC linear sensor						
	Accuracy	TC inputs: Calibration accuracy: < +/- (0.25% of reading value in °C +0,1°C) Linearization accuracy: 0.1% of reading value Cold junction accuracy: < +/- 1.5°C at 25°C room temperature) Cold junction compensation: > 30:1 rejection to the change of the room temperature RTD input: Calibration accuracy: < +/- (0.15% of reading value in °C +1°C) Temperature drift: < +/- (0.005% of reading value in °C +0.015°C)/°C from 25°C room temperature Linearization accuracy: 0.1% of reading value Linear inputs: Calibration accuracy< 0.1% full scale Temperature drift: < +/- 0.005% full scale /°C at 25°C room temperature						
	Sampling time	60 ms / 120 ms, selectable						
	Digital filter	0.0...20.0 s						
	Temperature unit of measurement	Degrees C / F, selectable from keypad						
	Signal interval	Type: linear Scale: -1999...9999, settable decimal point						
	TC (thermocouple) input	Thermocouple: J, K, R, S, T, C, D; Linearization: ITS90 or custom;						
	RTD (resistance thermometer) input	Resistance thermometer: PT100, JPT100; Input impedance (Ri): ≥ 30 kΩ; Linearization: DIN 43760 or custom; Max. line resistance: 20 Ω						
	DC linear input	0...60 mV		input impedance (Ri): > 70 kΩ				
		0...1 V		input impedance (Ri): > 15 kΩ				
0...5 V / 0...10 V		input impedance (Ri): > 30 kΩ						
0/4...20 mA		input impedance (Ri): 50 Ω						
		Linearization: linear or custom						
AUXILIARY INPUT	Remote setpoint	0...1 V, 0...10 V, 0/4...20 mA						
	Scale	0...1 V 0...10 V 0/4...20 mA		input impedance (Ri): > 15 kΩ input impedance (Ri): > 10 kΩ input impedance (Ri): 50 Ω				
	Accuracy	0.1% f.s. ±1 digit @25 °C						
CT INPUT (ammeter)	Type	Isolated via external transformer						
	Accuracy	Number: 2 max - Max. capacity: x / 50 mA AC - Line frequency: 50/60 Hz - Input impedance (Ri): 10 Ω ±2% f.s. ±1 digit @25 °C						
DIGITAL INPUTS	Number	3 max			5 max			
	Type	voltage-free contact, or NPN 24 V - 4,5 mA, or PNP 12/24 V - max 3,6 mA.						
	Isolation	500 V						
OUTPUTS								
ALARMS	Relay (R)	Number: 4 max Type of relay contact: NO Max. current: 5 A, 250 VAC / 30 VDC,			Number: 4 max Type of relay contact: NO Max. current: 5 A, 250 VAC / 30 VDC, cos φ = 1			
	Logic (D)	Minimum load: 5 V, 10 mA - Life cycle: > 100,000 operations - Double isolation Number: 2 max - Type: for solid-state relays - Voltage: 24 V ±10% (min 10 V @20 mA) - Isolated from main input						
	Triac (long life relè) (T)	Number: 1 max Load: resistive Voltage: 75...264 VAC Current max: 1 A Isolation 3 kV; snubber circuit integrated zero crossing switching			Number: 1 max Load: resistive Voltage: 12...240 VAC Current max: 2 A Isolation 2.5 kV zero crossing switching			


		STATOP 548	STATOP 589	STATOP 596
ALARMS	Continuous (C)	Number: 1 max Current: 4...20mA $R_{out} < 500 \Omega$ Resolution: 12 bit Isolated from main input		
	Analog retransmission (A1)	Number: 1 max Signal: 10V, 0/4...20mA 0...10 V, max 20 mA, $R_{out} > 500 \Omega$ 0...20 mA, 4...20 mA, $R_{out} < 500 \Omega$ Resolution: 12 bit Isolated from main input		
	Number of alarm functions	4 max, assignable to an output		
	Possible configurations	Maximum, minimum, symmetric, absolute/relative, exclusion at firing, memory, reset from keypad and/or contact, LBA, HB, HBB Hold Back Band if enabled with Programmer function		
CONTROL FUNCTIONS				
CONTROL	Type	Single loop		
	Control	PID, ON/OFF, single action heat or cool, double action heat/cool		
	Control output	Continuous or ON/OFF Cycle time: constant or optimized (BF)		
	Control output for motorized valves	OPEN/CLOSE for floating motorized valve on Relay, Solid-state, Triac outputs		
SETPOINT PROGRAMMER	Number of programs	Max 4, Start / Stop / Reset / Skip via digital inputs and/or outputs from logic operations Output state: Run /Hold / Ready / End		
	Number of steps	Max 12, each with own setpoint, ramp time and hold time; Times settable in HH:MM or MM:SS Max 4 consents, configurable for ramp and for hold Max 4 events, configurable in ramp and in hold		
MULTIPLE SETPOINTS	Number of setpoint	Max 4, selectable from digital input Each setpoint change is subject to set ramp, different for up and down ramp		
LOGIC ¹ OPERATIONS	Function blocks	Max 16, with 4 input variables per block. The result can act on the state of the controller, of the programmer on alarms and outputs. Each function contains an incorporated timer block timer.		
TIMER FUNCTION	Modes	START / STOP STABILIZATION (timer is on when PV enters a band set around setpoint; at end of count you can activate an output, shut down SW or change SP1/SP2) FIRING (timed activation of control after power on)		
ENERGY COUNTER		Calculation done on nominal line voltage and nominal load power or on rms current measured on load via CT		
DIAGNOSTIC		Short circuit or open circuit (LBA alarm) Interrupted or partially interrupted load (HB alarm) Short circuit of control output (SSR alarm)		
RETENTIVE MEMORY	Type	EEPROM		
	Max. number of writes	1,000,000		
SERIAL INTERFACE				
		Type: RS485 Baudrate: 1200, 2400, 4800, 9600, 19,200, 38,400, 57,600, 115,200 bit/s Protocol: MODBUS RTU Isolated from main input		
GENERAL DATA				
POWER SUPPLY	Operating voltage	100...240 VAC/VDC $\pm 10\%$, 50/60 Hz (on request 20...27 VAC/VDC $\pm 10\%$)		
	Power dissipation	5 W max	10 W max	10 W max
	Protections	Overvoltage 300 V / 35 V		
	Connection	Screw terminals and crimp connector, max. wire section 1 mm ²		
CONNECTIONS	Serial configuration port (for USB connection)	Connector: microUSB		
	Inputs and outputs	Screw terminals and crimp connector, max. wire section 2,5 mm ²		
AMBIENT CONDITIONS	Use	Indoor		
	Altitude	2000 m max		
	Operating temperature	-10 ... +55 °C (as per IEC 68-2-14)		
	Storage temperature	-20 ... +70 °C (as per IEC 68-2-14)		
PROTECTION LEVEL	Relative humidity	20...85% RH non-condensing (as per IEC 68-2-3)		
		IP 65 on front panel (as per IEC 68-2-3)		
ASSEMBLY	Positioning	On panel, removable faceplate		
	Installation regulations	Installation category: II; Pollution degree: 2, Isolation: double		
DIMENSIONS		48X48 mm (1/16 DIN), Depth.: 80 mm	48X96 mm (1/8 DIN) Depth.: 80 mm	96X96 mm (1/4 DIN) Depth.: 80 mm
WEIGHT		0.16 kg	0.24 kg	0.24 kg
CE STANDARDS	EMC (electromagnetic compatibility)	EMC p(electromagnetic compatibility): conforms to directive 2014/30/EU with reference to standard EN 61326-1 emission in industrial environment class A for models 650 LV emission in residential environment class B for models 650 HV Safety LVD: conforms to directive 2014/35/EU with reference to standard EN61010-1		
	UL	Conformity C/UL/US File no. E494863		
OTHER ELEMENTS				
ACCESSORIES		Programming cable for PC, USB - micro USB connectors, lenght 1,8 m		
		Current transformer (CT) 50/0.05 A		
		Current transformer (CT) 25/0.05 A		

PID CONTROLLERS - 500 SERIES


STATOP 548 connections




OPTIONS



LEGEND



STATOP 589 / 596 connections



LEGEND


~ PWR Power supply
~ ~
+ Linear input in voltage/current
-
Input for current transformer
SPR + Remote Set-point
SPR -

Isolated digital inputs
Thermocouple input
Input PT100 JPT100 2 / 3 wires

Relay output
Long-life solid state relay output
Isolated analog output
Logic output

A (Data +) RS485 serial line
B (Data -)

STATOP 548 / 589 / 596 Input/Output specifications



PID CONTROLLERS - 500 SERIES

To order

STATOP 548 controller

Power supply 100...240 VAC

Code	Model	Valves	Programmer	Inputs			Outputs					RS485	Logic functions	Total Number of Outputs
				Digital	CT	SPR	Relay	Triac	Logic	Analog I	Analog V/I			
LST548C-002	STATOP548C-D-R00-00000-1-P						1		1					2 outputs
LST548C-001	STATOP548C-R-R00-00000-1-P						2							
LST548C-004	STATOP548C-D-R00-00120-1-P			2	1		1		1					
LST548C-003	STATOP548C-D-RR0-00000-1-P						2		1					3 outputs
LST548C-005	STATOP548C-R-RR0-00000-1-P						3							
LST548C-009	STATOP548C-R-RT0-00000-1-P						2	1						
LST548C-010	STATOP548C-D-RR0-00030-1-P			3			2		1					
LST548C-007	STATOP548C-D-RR0-00200-1-P				2		2		1					
LST548C-006	STATOP548C-C-RR0-00000-1-P						2			1				
LST548C-008	STATOP548C-D-R00-01030-1-P			3			1		1		1			4 outputs
LST548C-014	STATOP548C-R-R00-01030-1-P			3			2				1			
LST548C-012	STATOP548C-R-RR0-00101-1-P				1		3					•		
LST548C-011	STATOP548C-D-RRR-00000-1-P						3		1					
LST548C-015	STATOP548C-R-RRR-00000-1-P						4							
LST548C-013	STATOP548C-D-RRR-00220-1LFP			2	2		3		1				•	
LST548C-016	STATOP548C-D-RRR-00031-1LFP			3			3		1			•	•	
LST548C-019	STATOP548C-D-RRR-00201-1LFP				2		3		1			•	•	
LST548C-020	STATOP548C-D-RR0-01011-1LFP			1			2		1		1	•	•	
LST548C-017	STATOP548C-C-RRR-10030-1LFP			3		1	3			1			•	
LST548V-018	STATOP548V-R-RRR-00000-1-P	•					4							5 outputs
LST548V-022	STATOP548V-R-RRR-00030-1-P	•		3			4							
LST548P-023	STATOP548P-D-RRR-00000-1-P		•				3		1					
LST548P-021	STATOP548P-D-RRR-00030-1LFP		•	3			3		1				•	
LST548C-024	STATOP548C-D-RRR-01030-1LFP			3			3		1		1		•	

STATOP 589 controller

Power supply 100...240 VAC

Code	Model	Valves	Programmer	Inputs			Outputs					RS485	Logic functions	Total Number of Outputs
				Digital	CT	SPR	Relay	Triac	Logic	Analog I	Analog V/I			
LST589C-001	STATOP589C-D-R00-00000-1-P						1		1					2 outputs
LST589C-002	STATOP589C-R-R00-00000-1-P						2							
LST589C-003	STATOP589C-D-R00-00150-1-P			5	1		1		1					
LST589C-004	STATOP589C-D-RR0-00000-1-P						2		1					3 outputs
LST589C-005	STATOP589C-R-RR0-00000-1-P						3							
LST589C-006	STATOP589C-D-RR0-00050-1-P			5			2		1					
LST589C-007	STATOP589C-D-RR0-00200-1-P				2		2		1					
LST589C-008	STATOP589C-C-RR0-00000-1-P						2			1				
LST589C-009	STATOP589C-D-R00-01050-1-P			5			1		1		1			4 outputs
LST589C-010	STATOP589C-R-R00-01050-1-P			5			2				1			
LST589C-011	STATOP589C-R-RR0-00101-1-P				1		3					•		
LST589C-012	STATOP589C-D-RRR-00000-1-P						3		1					
LST589C-013	STATOP589C-R-RRR-00000-1-P						4							
LST589C-015	STATOP589C-R-RRT-00000-1-P						3	1						
LST589C-014	STATOP589C-D-RRR-00250-1LFP			5	2		3		1				•	
LST589C-016	STATOP589C-D-RRR-00051-1LFP			5			3		1			•	•	
LST589C-017	STATOP589C-C-DRR-00051-1LFP			5			2		1	1		•	•	
LST589C-018	STATOP589C-D-RRR-00201-1LFP				2		3		1			•	•	
LST589C-019	STATOP589C-C-RRR-10050-1LFP			5		1	3			1			•	
LST589V-020	STATOP589V-R-RRR-00000-1-P	•					4							5 outputs
LST589V-021	STATOP589V-R-RRR-00050-1-P	•		5			4							
LST589P-022	STATOP589P-D-RRR-00000-1-P		•				3		1					
LST589P-023	STATOP589P-D-RRR-00050-1LFP		•	5			3		1				•	
LST589C-024	STATOP589C-D-RRR-01050-1LFP			5			3		1		1		•	

STATOP 596 controller

Power supply 100...240 VAC/VDC

Code	Model	Valves	Programmer	Inputs			Outputs					Logic functions	Total Number of Outputs
				Digital	CT	SPR	Relay	Triac	Logic	Analog I	Analog V/I		
LST596C-001	STATOP596C-D-R00-00000-1-P						1		1				2 outputs
LST596C-002	STATOP596C-R-R00-00000-1-P						2						
LST596C-003	STATOP596C-D-R00-00150-1-P			5	1		1		1				3 outputs
LST596C-004	STATOP596C-D-RR0-00000-1-P						2		1				
LST596C-005	STATOP596C-R-RR0-00000-1-P						3						
LST596C-006	STATOP596C-D-RR0-00050-1-P			5			2		1				
LST596C-007	STATOP596C-D-RR0-00200-1-P				2		2		1				
LST596C-008	STATOP596C-C-RR0-00000-1-P						2			1			
LST596C-009	STATOP596C-D-R00-01050-1-P			5			1		1		1		4 outputs
LST596C-010	STATOP596C-R-R00-01050-1-P			5			2				1		
LST596C-011	STATOP596C-R-RR0-00101-1-P				1		3					•	
LST596C-012	STATOP596C-D-RRR-00000-1-P						3		1				
LST596C-013	STATOP596C-R-RRR-00000-1-P						4						
LST596C-014	STATOP596C-R-RRT-00000-1-P						3	1					
LST596C-015	STATOP596C-D-RRR-00250-1LFP			5	2		3		1			•	5 outputs
LST596C-016	STATOP596C-D-RRR-00051-1LFP			5			3		1			•	
LST596C-017	STATOP596C-C-RRR-00051-1LFP			5			2		1	1		•	
LST596C-018	STATOP596C-D-RRR-00201-1LFP				2		3		1			•	
LST596C-019	STATOP596C-C-RRR-10050-1LFP			5		1	3			1		•	
LST596V-020	STATOP596V-R-RRR-00000-1-P	•					4						
LST596V-021	STATOP596V-R-RRR-00050-1-P	•		5			4						
LST596P-022	STATOP596P-D-RRR-00000-1-P		•				3		1				
LST596P-023	STATOP596P-D-RRR-00050-1LFP		•	5			3		1			•	
LST596C-024	STATOP596C-D-RRR-01050-1LFP			5			3		1		1	•	



**The STATOP Series
is also available with
a 20...27 VAC/ VDC
power supply.**

Find all the references of the 500 Series at our website www.pyrocontrole.com
Our teams are always ready to listen.

For further information

Tel: + 33 4 72 14 15 40

Email: info@pyrocontrole.com

10 subsidiaries worldwide

GERMANY

Chauvin Arnoux GmbH
Ohmstraße 1
77694 KEHL / RHEIN
Tél. : +49 7851 99 26-0
Fax : +49 7851 99 26-60
info@chauvin-arnoux.de
www.chauvin-arnoux.de

AUSTRIA

Chauvin Arnoux Ges.m.b.H
Slamastrasse 29/2/4
1230 WIEN
Tél. : +43 1 61 61 9 61
Fax : +43 1 61 61 9 61-61
vie-office@chauvin-arnoux.at
www.chauvin-arnoux.at

CHINA

Shanghai Pujiang Enerdis Instruments Co Ltd
3rd Floor, 23 Building, Gemdale Viseen
Minhang Technology & Industrial Park,
1288 lane, Zhongchun Road, Minhang
District, SHANGHAI, CHINA
Tel: 00 86 21 65215196
Fax: 00 86 21 65216107

SPAIN

Chauvin Arnoux Ibérica SA
C/ Roger de Flor N°293
1a Planta
08025 BARCELONA
Tél. : +34 902 20 22 26
Fax : +34 934 59 14 43
info@chauvin-arnoux.es
www.chauvin-arnoux.es

ITALY

AMRA SpA
Via Sant'Ambrogio, 23
20846 MACHERIO (MB)
Tél. : +39 039 245 75 45
Fax : +39 039 481 561
info@amra-chauvin-arnoux.it
www.chauvin-arnoux.it

MIDDLE EAST

Chauvin Arnoux Middle East
PO Box 60-154
1241 2020 JAL EL DIB
(Beyrouth) - LIBAN
Tél. : +961 1 890 425
Fax : +961 1 890 424
camie@chauvin-arnoux.com
www.chauvin-arnoux.com

UNITED KINGDOM

Chauvin Arnoux Ltd
Unit 1 Nelson Ct, Flagship Sq
Shaw Cross Business Pk, Dewsbury
West Yorkshire - WF12 7TH
Tél. : +44 1924 460 494
Fax : +44 1924 455 328
info@chauvin-arnoux.co.uk
www.chauvin-arnoux.com

SCANDINAVIA

CA Mätssystem AB
Sjöflygvägen 35
SE-183 62 TABY
Tél. : +46 8 50 52 68 00
Fax : +46 8 50 52 68 10
info@camatsystem.com
www.camatsystem.com

SWITZERLAND

Chauvin Arnoux AG
Moosacherstrasse 15
8804 AU / ZH
Tél. : +41 44 727 75 55
Fax : +41 44 727 75 56
info@chauvin-arnoux.ch
www.chauvin-arnoux.ch

USA

Chauvin Arnoux Inc
d.b.a AEMC Instruments
15 Faraday Drive
Dover - NH 03820
Tél. : +1 (800) 945-2362
Fax : +1 (603) 742-2346
sales@aemc.com
www.aemc.com

Contact us:

PYROCONTROLE
6 bis avenue du Docteur Schweitzer
69881 MEYZIEU Cedex France

info@pyrocontrole.com



+33 4 72 14 15 40

Ask for our other
product catalogues

**CHAUVIN
ARNOUX**
PYROCONTROLE

Visit PYROCONTROLE at **www.pyrocontrole.com**

